### **Product data sheet**



## ACA-B706-025

## LHD Cable Accessory - Bracket "7", 60 mm (2.4") (Zintec) w/ Sleeve - Qty 25

## Pipe Clip

The ACA-B706 series 7-bracket (pipe clip) is designed to utilise existing pipework running through the protected area as a fixture for the liner heat detection cable. The ACA-B706 is designed to fit any pipe diameter. A silicon protection sleeve is supplied with the unit to protect the linear heat cable when fastened to the bracket.

#### Installation

The ACA-B706 should be fitted to the underside of the pipe and secured in place using suitable cable ties or strapping. The hole in the end of the bracket allows for the securing of the sensor cable using a silicone sleeve and cable tie. Alternatively an I-bracket (distance piece) may be connected to the 7-bracket to extend the position of the sensor cable. Without an extension the 7-bracket (pipe clip) supports the sensor cable approx. 60mm below the pipe.

Recommended spacing: 1m



#### **Details**

- Easy installation of linear heat cable
- For use on existing pipes in the area
- · Available in zintec
- Available in quantities of 25

# ACA-B706-025

## LHD Cable Accessory - Bracket "7", 60 mm (2.4") (Zintec) w/ Sleeve - Qty 25

### **Technical specifications**

Physical		
Physical dimensions	20 x 60 x 50 mm (W x H X D)	
Net weight	850 g	
Environmental		
Environment	Indoor, Outdoor	
Dimensions (h x v	w x d)	
	60 x 20 x 50 mm	
- ACA-B706-025		
Weight	850g	
Material	Zintec	
Quantity	25	
- ACA-B706-100		
Weight	3.4 kg	
Material	Zintec	
Quantity	100	
- ACA-B706SS-02	25	
Weight	580g	
Material	Stainless Steel	
Quantity	25	
- ACA-B706SS-10	00	
Weight	2.3kg	
Material	Stainless Steel	
Quantity	100	

