

DB952IAS

950 Series Integrated Base Sounder With Isolator

General

The DB952IAS is a range of integrated, self monitoring base sounders with integral short-circuit isolator for use on Series 950 and Series 990 systems. They incorporate a base into which a series 950 or 990 detector, or beacon can be fitted. It may also be used with a red (AS952CAP-R) or white (AS952CAP-W) cap for stand-alone use.

Tones

The DB952IAS sounders support multiple tones. A low tone range is useful in areas such as hospitals where a fire alert is initially intended to warn staff only. The sounder may be set to the high range for general use.

In addition to the standard tones in the DB952IAS, a slow whoop tone to Dutch standard NEN2575 is available in the DB952IAS-NEN, as well as a German standard DIN tone version in the DB952IAS-DIN.

Syncronisation

Syncronisation of tones ensures the integrity of the signal—tones from different sounders do not merge into one signal that could be mistaken for a different tone. DB952IAS sounders are synchronised with each other in both 'alert' and 'evacuate' modes.

Self Test

The acoustic self-test means that the sounder listens to itself when it is switched on. If no sound is detected a fault signal is transmitted when the sounder is polled.

The same self-test feature may also be used during commissioning or periodical maintenance testing. The sounder may simply be activated for at least 5 seconds and the control panel checked for a fault signal. If none is received, the sounder is working properly.



Details

- Two tone ranges 55 to 75 dB and 75 to 91 dB
- Synchronisation of 'alert' and 'evacuate' tones
- Individual sounder addressing
- Available with built-in isolator
- Acoustic self-test
- Slow whoop option available

DB952IAS

950 Series Integrated Base Sounder With Isolator

Technical specifications

Electrical

Operating voltage	17 to 28 VDC
-------------------	--------------

Environmental

Operating temperature	-20 to +60°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP21D

Standards & regulation

Certification	EN54-17, EN54-3
---------------	-----------------

Operating voltages

Protocol pulses	5 - 9 V
-----------------	---------

Current consumption at 24 V

Switch-on surge, <1s	1.2 mA
Quiescent	200 µA
Sounder operated 50 - 75 dB	5 mA
Sounder operated 75 - 91dB	5 mA

Sound output

Maximum at 90°	91db(A)
Maximum to EN54	83dB(A)
Sound pressure level	Tone dependent



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 4 October 2021 - 15:43