Product data sheet



119551

950 Series Zone Monitor Unit with Isolator (Surface Mount)

General

The II955I addressable conventional zone monitor powers and controls the operation of one zone of conventional detectors directly from the analogue loop. Provision is also made for either standard end-of-line supervision, or the inclusion of active end-of-line devices to allow for head-out monitoring.

Design

The II955I is designed to be surface mounted to walls and consists of three parts:

- a backbox with knockouts for cable entry
- a PCB assembly
- a protective front cover.

The II955I is fitted with a bi-directional short-circuit isolator so that they are unaffected by a single short-circuit on either loop input or output.



Details

- · Aesthetically pleasing
- Loop powered
- Part of a full line consisting of: Switch monitors Zone monitors Input/output units • Sounder circuit controllers
- LEDs for signalling of I/O and fault condition
- On board loop isolation
- Standard or head-out supervision
- EN54 and CPD certified

119551

Capacitance

950 Series Zone Monitor Unit with Isolator (Surface Mount)

Technical specifications

14 to 28 VDC
<4 mA
14 - 28 VDC
5 - 9 V
3.5 mA
4 mA
19 mA
11 mA
150 x 90 x 48 mm
White
150 x 90 x 48 mm
-20 to +70°C
0 to 95% noncondensing
Indoor
IP54
-20 to 70°C
0 - 95 %
IP54
ation
EN54-17, EN54-18
es
19 V ± 1V (loop voltage -1.5 V)
5.1 kohm 1/3 W (or active)

< 50 μF



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.