

# NC-DPM-W

## Conventional multisensor fire detector (White)

### General

---

The NC-DPM-W is an optical and heat multisensor detector. It combines photoelectric (optical) detection, fixed temperature and rate-of-rise detection technology. The smoke and heat sensors are integrated to provide a solution to a wide range of applications, allowing detection of more complex fire types. Amongst these include fire types generating black smoke as well as small particles fires such as those from burning alcohol.

### Application

---

The detector supports installation on the NC-DB-W conventional detector base for standard applications, or the NC-DBD-W diode base when head-out functionality to BS5839 standard is required. Detection sensitivities are programmable using the NC-D-PT device programmer.



### Details

---

- Supports drift compensation to enable good environmental adaptability
- Self-diagnostic
- Local test activation with reed switch
- Chamber contamination checking
- All round LED visibility (360° viewing angle) avoids time spent on specific detector orientation
- Configurable polling LED support
- Remote indicator output
- 2 Programmable smoke sensitivity levels

# NC-DPM-W

## Conventional multisensor fire detector (White)

### Technical specifications

#### General

Status indication	Red LED
User interface	Via LED - polling, fault, contamination and alarm
Compatibility	GST100A Series conventional CIEs as well as GST I-9319 Zone Monitor
Reset voltage	<1 VDC
Reset time	<10 s
Alarm levels	2
Connectivity	Zone connection - 2-core (polarity sensitive), RI connection - 2-core (polarity sensitive)

#### Electrical

Operating voltage	9.5 to 28 VDC (24 VDC typical)
Current consumption	<60 $\mu$ A (Quiescent) $\leq$ 55 mA (Alarm)
Cable specification	>1.0 mm <sup>2</sup>
No. of cable cores	2
Terminals	4

#### Detection

Detection principle	Optical & Heat
Sensitivity	Programmable
Zone length	Panel dependent
Heat Class	A2R
Activation temperature	62°C

#### Output

Remote alarm output	1
---------------------	---

#### Physical

Physical dimensions	54.5 mm (including base) x 100 mm $\varnothing$
Net weight	$\pm$ 110 g
Colour	Traffic white (RAL9016)
Mounting type	Ceiling mount
Material (body)	ABS

#### Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP2x

#### Regulatory

Compliance	CE, WEEE
Certification	EN54-5, EN54-7
Voluntary marks	BOSEC
Standards	LPCB

#### Compatible products

Category	Reference	Description
Detection device	NC-D-PT	Conventional hand held device programmer
Detection device	NC-DB-W	Conventional standard point detector base (White)
Detection device	NC-DB2R-W	Conventional dual relay base (White)
Detection device	NC-DBD-W	Conventional standard point detector base with diode (White)
Detection device	NC-DBR-W	Conventional relay base (White)
Notification device	PA25/3L	Conventional remote indicator device

